

The Coastal Range - Technical Dimensions

Model	Height	Width	Pipe Centres	Pipe centre from the wall*	Projection*	Dual fuel element Watts	Heat Output C/H format		Bracket position			Weight Kg
							BTU	Watts	Centres	from top	from bottom	
Fisher 300	700mm	300mm	270mm	102mm	115mm	100	1068	313	270mm	120mm	110mm	4.80
Fisher 400	700mm	400mm	370mm	102mm	115mm	100	1380	404	370mm	120mm	110mm	5.20
Fisher 520	700mm	520mm	490mm	102mm	115mm	150	1500	440	490mm	120mm	110mm	5.60
Fisher 620	700mm	620mm	590mm	102mm	115mm	150	1648	483	590mm	120mm	110mm	6.66
Humber 400 <i>Curved Front</i>	700mm	400mm	370mm	102mm	140mm	150	1449	425	370mm	120mm	110mm	5.40
Humber 520 <i>Curved Front</i>	700mm	520mm	490mm	102mm	165mm	150	1600	469	490mm	120mm	110mm	6.72
Humber 620 <i>Curved Front</i>	700mm	620mm	590mm	102mm	165mm	150	1763	517	590mm	120mm	110mm	7.80
Viking 300	1250mm	300mm	270mm	102mm	115mm	200	2106	617	270mm	120mm	110mm	7.50
Viking 400	1250mm	400mm	370mm	102mm	115mm	200	2368	694	370mm	120mm	110mm	8.30
Viking 520	1250mm	520mm	490mm	102mm	115mm	200	2500	733	490mm	120mm	110mm	9.38
Viking 620	1250mm	620mm	590mm	102mm	115mm	250	2726	799	590mm	120mm	110mm	10.88
Portland 400 <i>Curved Front</i>	1250mm	400mm	370mm	102mm	140mm	200	2486	728	370mm	120mm	110mm	8.50
Portland 520 <i>Curved Front</i>	1250mm	520mm	490mm	102mm	165mm	250	2600	762	490mm	120mm	110mm	9.76
Portland 620 <i>Curved Front</i>	1250mm	620mm	590mm	102mm	165mm	250	2841	832	590mm	120mm	110mm	11.80
Plymouth 750	600mm	750mm	720mm	102mm	115mm	150	1676	491	720mm	120mm	110mm	7.10
Plymouth 1000	600mm	1000mm	970mm	102mm	115mm	200	1885	552	970mm	120mm	110mm	8.60
Biscay	780mm	500mm	470mm	102mm	115mm	200	1998	585	470mm	120mm	110mm	8.40
Thames	1191mm	600mm	570mm	102mm	115mm	300	2859	838	570mm	120mm	110mm	13.50
Tyne	370mm	520mm	490mm	102mm	115mm	70	410	120	490mm	120mm	110mm	2.66
Dover	700mm	520mm	490mm	102mm	115mm	100	740	217	490mm	120mm	110mm	3.90
Shannon 1460/360	1460mm	360mm	300mm	55mm	75mm	300	2406	705	Variable			12.20
Shannon 1460/530	1460mm	530mm	470mm	55mm	75mm	300	2785	816	Variable			18.00
Shannon 1460/710	1460mm	710mm	650mm	55mm	75mm	500	3498	1025	Variable			24.00
Shannon 1660/360	1660mm	360mm	300mm	55mm	75mm	500	2944	863	Variable			13.50
Shannon 1660/530	1660mm	530mm	470mm	55mm	75mm	500	3408	999	Variable			20.30
Malin 1460/272	1460mm	275mm	215mm	65mm	80mm	300	2154	631	175mm	85mm	0mm	13.10
Malin 1460/360	1460mm	360mm	300mm	65mm	80mm	300	2839	832	260mm	85mm	0mm	17.60
Malin 1460/535	1460mm	535mm	475mm	65mm	80mm	500	3676	1077	435mm	85mm	0mm	25.80
Malin 1960/275	1960mm	275mm	215mm	65mm	80mm	500	2805	822	175mm	85mm	0mm	17.50
Malin 1960/360	1960mm	360mm	300mm	65mm	80mm	500	3715	1088	260mm	85mm	0mm	21.50
Malin 1960/535	1960mm	535mm	475mm	65mm	80mm	500	4210	1234	435mm	85mm	0mm	34.00

* Standard brackets measurement, shortened brackets available to reduce projection/centres by 25mm. Not applicable for Malin and Shannon.

Heat output figures are for central heating versions. BTU/Watt figures are based on $\Delta T=60K$.

All radiators are manufactured from 100% Stainless Steel and can be used on all systems including open/hot water systems.

JIS Europe Ltd, Warehouse 2, Nash Lane, Scaynes Hill, Haywards Heath, West Sussex, RH17 7NJ, U.K.

Tel No: +44 (0)1444 831200 Fax No: +44 (0)1444 831900 email: info@jiseurope.co.uk

www.thecoastalrange.co.uk